

f t in

MODEL **TC**3000/50-4

Max amps

HIGH POWER, MULTIPLE START AND CONTINUOUS DC POWER UNIT

NATO S/N 2995-99-488-6417



SUPPLIED WITH UNIT Output Cable

OPTIONAL EXTRAS	
Towbar	

Handlebar and Casters Various Output Cable Lengths Various Connectors

PROTECTION

- Overload.
- Over Voltage.
- Over Current.
- Short Circuit.
- 30mA RCD.
- Thermal Management.

	5200 (Max. short circuit current)	
Capacity	76 Amp Hrs @ 10 Hr rate	
Max Start Voltage	26V DC	
Continuous voltage	28.5v DC	
Continuous power	50 amps	
AC input	95v - 270v	
Size (cm)	L89 W78 H46	
Weight nom kg	115	
Operating Temp	-40°C - + 50° C	
Case	Zinc Coated Steel	
Voltage indication	LED display	
Performance monitoring	LED display	
Output Cable	3m heavy duty cable with aircraft connector	
Charger	50A Electronic inbuilt. Charging time less than 1 hour from 50%.	
Plug Selector		
UK	240V 13A (STANDARD MAINS)	
USA	110V 15A (STANDARD MAINS)	
Other Countries	Please state country when ordering	

TC3000/50-4 3500 (Nom. short circut current)

Specification may change without notice

• Weather protected.

- Air transportable, 'Non Hazardous'
- Maintenance free.
- Tough and compact.
- · No memory effect.
- High charge retention.
- · Long shelf life.
- · Fast recharge.
- No cycling.
- \cdot Leak proof.
- Cells replaceable on condition.
- Multiple, heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.
- · Continuous 28V DC power supply
- Starts Main Battle Tanks.
- Starts Armoured Fighting Vehicles.
- \cdot Portable start power at remote locations.

www.redboxint.com sales@redboxint.com Tel +44 (0) 1794 518888 Fax +44 (0) 1794 518848