



ELECTRA-X

CONTACT CLEANER



FEATURES

- Non-flammable
- Quick penetration
- Fast evaporating
- Non-conductive
- Contains no chlorinated solvents
- No residue
- Safe on most surfaces
- Removes oil, grease, and dirt
- Conforms to CARB (California Air Resources Board) VOC requirements

APPLICATIONS

- Armatures
- Contacts
- Electric Motors
- Electric Relays
- Generators
- Panels
- Printed Circuits
- Switches



PACKAGE

Net Fill
12 oz. (340 grams) aerosol

Part No.
00816

PROPERTIES

KB Value:
80

Specific Gravity:
1.30 @ 77°F (25°C)

% Non-Volatiles:
<100 ppm

V.O.C. Content:
70% (complies with
C.A.R.B. requirements)

Dielectric Strength and
Breakdown Voltage
(ASTM D-877):
9,000 Volts

Flash Point:
None

Propellant:
HFC 134a

Value Performance

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2009 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2219 • Rev. 1/2009