

PRODUCT DATA SHEET

NOPOP™ RETARDER ADDITIVE PTI ADDITIVES

DESCRIPTION

PTI NoPop™ Retarder is a specially formulated solvent that is not photochemically reactive. This product is used as an additive to slow down the dry time of fast drying paints and primer. During hot and dry temperatures, coatings have a tendency to “solvent pop” and/or “dry spray”, small air bubbles form at the surface of the paint or when the paint dries before it hits the substrate. Retarders keep the material “wet” allowing it to flow, dry, and cure as it should.

COATING PROPERTIES & CHARACTERISTICS

| | |
|----------------------------------|-------------|
| Flash Point | 212°F |
| Weight (lbs per gallon) | 7.92 lbs |
| Color | Clear |
| Volatile Organic Compounds (VOC) | 950 g/l |
| Specifications | Proprietary |

SHELF LIFE

Shelf life is only applicable for materials stored in unopened and undamaged original factory filled containers. 1 year when stored between 50°-85° Fahrenheit.

MIXING INSTRUCTIONS

Add 8 fluid ounces of Retarder to 1 gallon of material or 2 fluid ounces to 1 quart of material.

- In a 2 component system, always add the Retarder to the component A. (paint) Mix well. Admix with the Component B (catalyst) as required.

HEALTH, SAFETY, & STORAGE REQUIREMENTS

Refer to each individual material SDS (Safety Data Sheet) for specific requirements on the health, safety, storage and handling requirements. Follow all local, state, and national regulations during surface preparation, material application and cleanup.

PRODUCT INFORMATION & DISCLAIMER

Product Data Sheets are periodically updated to reflect new information. It is important to use the latest and most recent revision for the product being used. The foregoing information is accurate to the best of our knowledge. However, due to differences in customer handling, use and method of application which are not known and are beyond our control, Products Techniques, Inc. makes no warranties as to the end result.