

Certified Coatings Products Co.

Safety Data Sheet

Revision 1
Prepared 2014-05-13

SECTION 1 - PRODUCT & COMPANY INFORMATION

Product Name: PTI PAINT REMOVER GREEN, FOR AIRCRAFT, MARINE & AUTOMOTIVE
TradeName(s):

Product Code: PTI-PRG

Products/Techniques, Inc.
dba Certified Coatings Products Co.
3271 S. Riverside Ave.
Bloomington, CA 92316

PH: 909.877.3951
FX: 909.877.6078
E-mail: pti@ptipaint.com
Web: www.ptipaint.com

CHEMTREC: 1.800.424.9300

OPERATING HOURS: 8:00 am - 4:30 pm PDT

SECTION 2 - HAZARDS IDENTIFICATION

HMIS:230X

GHS Ratings

Flammable liquid 1

GHS Hazards

H223	Flammable material
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H316	Causes mild skin irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H340	May cause genetic defects
H350	May cause cancer

GHS Precautions

P102	Keep out of reach of children
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P235	Keep cool
P260	Do not breathe dust/fume/gas/mist/vapours/spray
P262	Do not get in eyes, on skin, or on clothing
P263	Avoid contact during pregnancy/while nursing
P264	Wash ... thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection
P284	Wear respiratory protection
P361	Remove/Take off immediately all contaminated clothing
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician



Routes of Entry:

PTI-PRG

Inhalation Skin Contact Eye Contact Ingestion
 Exposure to this material may affect the following organs:
 Eyes Kidneys Liver Central Nervous System Skin Cardiovascular System
 GI Tract Respiratory System

ACUTE TOXICITY:

INHALATION: **Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.**

Effects of Overexposure, :

CARCINOGENICITY:

DICHLOROMETHANE: NTP: Anticipated carcinogen
 IARC: Possible human carcinogen; 2B
 OSHA: Potential cancer hazard

CONDITIONS AGGRAVATED: Unknown.

CHRONIC EFFECTS: **Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.**

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

<u>Chemical Name / CAS No</u>	<u>OSHA Exposure Limits</u>	<u>ACGIH Exposure Limits</u>	<u>Other Exposure Limits</u>
DICHLOROMETHANE 75-09-2 79.77 percent	25 ppm TWA skin 125 ppm STEL skin 12.5 ppm Action Level skin	50 ppm TWA BEI	
METHANOL 67-56-1 12.05 percent	200 ppm TWA; 260 mg/m3 TWA	250 ppm STEL 200 ppm TWA	NIOSH: 200 ppm TWA; 260 mg/m3 TWA 250 ppm STEL; 325 mg/m3 STEL
WATER (1) 7732-18-5 4.03 percent	No TLV established	No PEL established	
WAX 8002-74-2 1.26 percent		2 mg/m3 TWA (fume)	NIOSH: 2 mg/m3 TWA (fume)
HYDROXYPROPYL METHYLCELLULOSE 9004-65-3 1.20 percent			DOW IHG 10 mg/m3
TOLUENE 108-88-3 0.827 percent	200 ppm TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 375 mg/m3 TWA 150 ppm STEL; 560 mg/m3 STEL
AMMONIA 7664-41-7 0.405 percent	50 ppm TWA; 35 mg/m3 TWA	35 ppm STEL 25 ppm TWA	NIOSH: 25 ppm TWA; 18 mg/m3 TWA 35 ppm STEL; 27 mg/m3 STEL
NORFOX (1) 143-18-0 0.396 percent	No TLV established	No PEL established	

SECTION 4 - FIRST AID MEASURES

INHALATION: If breathing problems occur during use, **LEAVE AREA IMMEDIATELY** and get fresh air. If breathing problems remain, **SEEK IMMEDIATE MEDICAL ATTENTION.**

EYE CONTACT: Flush eyes with large amounts of clean water for at least 20 minutes. Seek immediate medical attention.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and launder before re-use.

INGESTION: Do not induce vomiting. Get immediate medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 0 C (32 F)

Autoignition: Not established

LEL: 0.0 %

UEL: 16.0 %

All flashpoints: TCC

EXTINGUISHING MEDIA: Alcohol foam, carbon dioxide (CO₂), dry chemical, water spray/water fog extinguishing systems

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back. Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.** Empty drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner, or properly disposed of.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 - HANDLING & STORAGE

HANDLING: Wear all appropriate Personal Protective Equipment (PPE). Wear appropriate respiratory protection and ensure adequate ventilation at all times as vapors can accumulate over time in enclosed spaces and poorly ventilated areas. Use product in a way that minimizes splashes and/or creation of dust. Wash with soap and water thoroughly after each use.

STORAGE: Keep away from heat, sparks and flame. Keep container closed when not in use. Store in a cool dry area at a temperature between 50 and 95 degrees F. Do not store outside in direct sunlight.

SECTION 8 - EXPOSURE CONTROL AND PERSONAL PROTECTION

<u>Chemical Name / CAS No</u>	<u>OSHA Exposure Limits</u>	<u>ACGIH Exposure Limits</u>	<u>Other Exposure Limits</u>
75-09-2	25 ppm TWA skin 125 ppm STEL skin 12.5 ppm Action Level skin	50 ppm TWA BEI	
67-56-1	200 ppm TWA; 260 mg/m ³ TWA	250 ppm STEL 200 ppm TWA	NIOSH: 200 ppm TWA; 260 mg/m ³ TWA 250 ppm STEL; 325 mg/m ³ STEL
7732-18-5	No TLV established	No PEL established	
8002-74-2		2 mg/m ³ TWA (fume)	NIOSH: 2 mg/m ³ TWA (fume) DOW IHG 10 mg/m ³
9004-65-3			
108-88-3	200 ppm TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 375 mg/m ³ TWA 150 ppm STEL; 560 mg/m ³ STEL
7664-41-7	50 ppm TWA; 35 mg/m ³ TWA	35 ppm STEL 25 ppm TWA	NIOSH: 25 ppm TWA; 18 mg/m ³ TWA 35 ppm STEL; 27 mg/m ³ STEL
143-18-0	No TLV established	No PEL established	

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

VENTILATION & RESPIRATORY PROTECTION: Always follow all local, state, and federal laws and regulations regarding the use of respirators. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Wear a MSHA/NIOSH approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

ADMINISTRATIVE CONTROLS: All individual company safety policies should be reviewed to determine compliance with applicable Federal, State and local safety regulations. If a company determines that threshold limit values and air quality contaminant level have not been exceeded, then that company should set it's own policies regarding the use of respirators and other Personal Protective Equipment.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves, such as neoprene or solvent resistant nitrile. To prevent repeated or prolonged skin contact, wear impervious clothing such as a chemical suit, rubber boots, and/or chemical safety goggles plus a face shield if such should be necessary. If the equipment to be worn is not available or the type of equipment for a specific job is not known, consult a reputable safety equipment supply company. Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid prolonged or repeated contact with skin. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

This product exhibits the following properties under normal conditions:

Appearance	Pigmented liquid
Odor	Solvent like
Physical State	Liquid
Appearance	Pigmented liquid
Odor	Solvent like
Physical State	Liquid
Vapor Density	2.55
Vapor Pressure	386.1 mmHg
Boiling Range	0 to 100 °C, 32 to 212 °F
Wt% Solids	5.05
Weight/Gallon	9.69
VOC(g/l) Less H2O and Exempt Compounds	641.89
VOC(lbs/gal) Less H2O and Exempt Compounds	5.35
VOC (g/L) Material	149.52
Specific Gravity	1.16
% VOC (C.A.R.B)	12.88

SECTION 10 - REACTIVITY & STABILITY

STABILITY:

Stable

INCOMPATIBILITY (Materials to avoid): strong acids and bases, oxidizers, and selected amines.

CONDITIONS TO AVOID: Avoid all possible sources of ignition.

No Data

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide (CO) and carbon dioxide (CO₂). Other unknown hazardous products are possible.

No Data

Hazardous polymerization will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

DICHLOROMETHANE

LC50 76000 mg/m³ Inhalation Rat 4 hours

LD50 2000 mg/kg Oral Rat: >

METHANOL

LC50 83 mg/L Inhalation Rat 4 hours

LC50 64000 ppm Inhalation Rat 4 hours

LD50 5628 mg/kg Oral Rat

LD50 15800 mg/kg Dermal Rabbit

WATER

LD50 90 mL/kg Oral Rat: >

WAX

LD50 3750 mg/kg Oral Rat: >

LD50 3600 mg/kg Dermal Rabbit:>

HYDROXYPROPYL METHYLCELLULOSE

LD50 10000 mg/kg Oral Rats

TOLUENE

LC50 13 mg/L Inhalation Rat 4 hours

LC50 26700 ppm Inhalation Rat:> 1 hours

LD50 636 mg/kg Oral Rat

LD50 8390 mg/kg Dermal Rabbit

LD50 12124 mg/kg Dermal Rat

AMMONIA

LC50 5 mg/L Inhalation Rat 1 hours

LC50 2000 ppm Inhalation Rat 4 hours

LD50 350 mg/kg Oral Rat

NORFOX

LD50 5 g/kg Oral Rat: >

LD50 2 g/kg Dermal Rat:>

INHALATION: Headaches, dizziness, nausea, decreased blood pressure, change in heart rate, and cyanosis may result from overexposure to vapor. **Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.**

INGESTION: This material may be harmful or fatal if swallowed.

SKIN CONTACT: May cause sensitization or allergic reaction.

EYE CONTACT: Direct contact with liquid, exposure to vapors or mist may cause stinging, tearing, redness, swelling and eye damage.

SECTION 12 - ECOLOGICAL INFORMATION

No information available.

SECTION 13 - DISPOSAL CONSIDERATIONS

It is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition. Maximize material recovery for reuse or recycling.

It is the responsibility of the user to determine if the material is a RCRA "hazardous waste" at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more restrictive. Contact your regional US EPA office for guidance concerning case specific disposal issues.

Non-usable product is regulated by US EPA as hazardous material under the following codes:

PTI-PRG

SECTION 14 - TRANSPORTATION / SHIPPING INFORMATION

Hazardous Material! Ship according to all applicable local, state, and federal regulations regarding labeling and packaging requirements.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>HazardClass</u>
DOT	PAINT RELATED MATERIAL	3066	III	8

SECTION 15 - REGULATORY INFORMATION

Additional regulatory listings, where applicable.

The following chemicals are listed under California Proposition 65:

- 75-09-2 DICHLOROMETHANE 79.77 % Carcinogen, Mutagen
- 67-56-1 METHANOL 12.05 % Mutagen

The following chemicals appear on the New Jersey Right-To-Know Chemicals list:

- 67-56-1 METHANOL

The following chemicals appear on the Pennsylvania Right-To-Know list:

- 75-09-2 DICHLOROMETHANE 79.77 %
- 67-56-1 METHANOL 12.05 %

SARA HAZARD CATEGORY: The product has been reviewed according to the EPA 'Hazard Categories' promulgated under sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

- 75-09-2 DICHLOROMETHANE Acute Health Hazard, Chronic Health Hazard
- 67-56-1 METHANOL Fire Hazard, Acute Health Hazard
- 9004-65-3 HYDROXYPROPYL METHYLCELLULOSE Fire Hazard

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

- DICHLOROMETHANE 79.77 %

<u>Country</u>	<u>Regulation</u>	<u>All components listed</u>



The chemical substances listed below are not on the TSCA Section 8 Inventory:

SECTION 16 - OTHER INFORMATION

The information in this document is believed to be correct as of the date printed.

NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT OF THE HAZARDS RELATED TO ITS USE.

This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of his use thereof.

(C) Copyright, 2013 Products Techniques, Inc.

Hazardous Material Information System (HMIS)

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

HMIS & NFPA Hazard Rating

Legend

* = Chronic Health Hazard


0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

National Fire Protection Association (NFPA)



Approved: 2013-07-08