

1 Identification of the substance/mixture and of the company/undertaking

· **Product details**

· **Trade name:** 40523 Low VOC Rubberized Undercoating

· **Article number:** 40523

· **Application of the substance / the preparation** coating

· **Manufacturer/Supplier:**

SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225

· **Information department:**

cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· **Emergency information:** 24 HR EMERGENCY CHEMTREC 1-800-424-9300

2 Composition/information on ingredients

· **Chemical characterization**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

68476-86-8	Petroleum gases, liquefied, sweetened ⚠ H220; ⚠ H280; ⚠ H340; H350	13 - 30%
108-88-3	toluene ⚠ H225; ⚠ H361; H373; H304; ⚠ H315; H336	13 - 30%
79-20-9	methyl acetate ⚠ H225; ⚠ H319; H336	10 - 13%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene ⚠ H226; ⚠ H315; H319; H335	10 - 13%
67-64-1	acetone ⚠ H225; ⚠ H319; H336	7 - 10%
69430-35-9	Alicyclic hydrocarbon resin ⚠ H315; H319; H335	7 - 10%
9017-27-0	Alpha-methyl styrene/vinyl toluene copolymer ⚠ H315; H319; H335	5 - 7%
14807-96-6	Talc (Mg3H2(SiO3)4) ⚠ H315; H319; H335	5 - 7%
66070-58-4	Styrene-Ethylene/Butylene-Styrene block Copolymer ⚠ H315; H319; H335	5 - 7%

3 Hazards identification

· **Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS02 Flame

H222 Extremely flammable aerosol.

(Contd. on page 2)

Trade name: 40523 Low VOC Rubberized Undercoating

(Contd. of page 1)



GHS08 Health hazard

H340 May cause genetic defects.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Toxic

May cause cancer. May cause heritable genetic damage.



Harmful

Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child.



Irritant

Irritating to eyes, respiratory system and skin.



Extremely flammable

Extremely flammable.

Vapours may cause drowsiness and dizziness.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

Warning! Pressurized container.

Has a narcotizing effect.

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· **Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

· **Hazard pictograms**



GHS02



GHS07



GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Petroleum gases, liquefied, sweetened toluene

(Contd. on page 3)


Trade name: 40523 Low VOC Rubberized Undercoating

(Contd. of page 2)

· Hazard statements

Extremely flammable aerosol.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause genetic defects.
 May cause cancer.
 Suspected of damaging fertility or the unborn child.
 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Pressurized container: Do not pierce or burn, even after use.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with directives on hazardous materials.

· Code letter and hazard designation of product:


Toxic
 Extremely flammable

· Hazard-determining components of labelling:

Petroleum gases, liquefied, sweetened
 toluene

· Risk phrases:

May cause cancer.
 May cause heritable genetic damage.
 Extremely flammable.
 Irritating to eyes, respiratory system and skin.
 Also harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Possible risk of harm to the unborn child.
 Vapours may cause drowsiness and dizziness.

· Safety phrases:

Avoid exposure - obtain special instructions before use.
 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
 Wear suitable protective clothing, gloves and eye/face protection.
 In case of insufficient ventilation, wear suitable respiratory equipment.
 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
 This material and its container must be disposed of as hazardous waste.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
 72.7 % by mass of the contents are flammable

(Contd. on page 4)

Trade name: 40523 Low VOC Rubberized Undercoating

(Contd. of page 3)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	4	Fire = 4
REACTIVITY	0	Reactivity = 0

4 First aid measures

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

5 Firefighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

(Contd. on page 5)



Trade name: 40523 Low VOC Rubberized Undercoating

(Contd. of page 4)

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not gas tight seal receptacle.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

108-88-3 toluene

PEL ()	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL ()	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV ()	75 mg/m ³ , 20 ppm NIC-BEI

79-20-9 methyl acetate

PEL ()	610 mg/m ³ , 200 ppm
REL ()	Short-term value: 760 mg/m ³ , 250 ppm Long-term value: 610 mg/m ³ , 200 ppm
TLV ()	Short-term value: 757 mg/m ³ , 250 ppm Long-term value: 606 mg/m ³ , 200 ppm

67-64-1 acetone

PEL ()	2400 mg/m ³ , 1000 ppm
REL ()	590 mg/m ³ , 250 ppm
TLV ()	Short-term value: 1782 mg/m ³ , 750 ppm Long-term value: 1188 mg/m ³ , 500 ppm BEI

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

Trade name: 40523 Low VOC Rubberized Undercoating

(Contd. of page 5)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

· **Appearance:**

Form: Aerosol
Color: According to product specification
Odor: Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: < 0°C (< 32°F)

· **Flash point:** < 0°C (< 32°F)

· **Ignition temperature:** 455°C (851°F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower: 1.2 Vol %
Upper: 16.0 Vol %

· **Vapor pressure at 20°C (68°F):** 220 hPa (165 mm Hg)

· **Density at 20°C (68°F):** 0.84 g/cm³ (7.01 lbs/gal)

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

(Contd. on page 7)



Trade name: 40523 Low VOC Rubberized Undercoating

(Contd. of page 6)

· Solvent content:	
Organic solvents:	72.7 %
VOC content:	39.8 %
	327.0 g/l / 2.73 lb/gal
Solids content:	
	27.3 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Materials to be avoided:**
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
Carcinogenic.
The product can cause inheritable damage.

12 Ecological information

- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Product:**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Trade name: 40523 Low VOC Rubberized Undercoating

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **DOT regulations:**



- **Hazard class:** 2.1
- **Identification number:** UN1950
- **Packing group:** -
- **Proper shipping name (technical name):** AEROSOLS, flammable
- **Label:** 2.1
- **Remarks:** ORM-D 49CFR 173.150,156,or306

· **Land transport TDG (Canada) and ADR/RID (Europe):**



- **Hazard class:** 2 - 5F Gases
- **UN-Number:** 1950
- **Packaging group:** -
- **Label:** 2.1
- **Description of goods:** 1950 AEROSOLS

· **Maritime transport IMDG:**



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label:** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Propper shipping name:** AEROSOLS

· **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label:** 2.1

(Contd. on page 9)



Trade name: 40523 Low VOC Rubberized Undercoating

(Contd. of page 8)

- **Packaging group:** -
- **Propper shipping name:** AEROSOLS, flammable
- **UN "Model Regulation":** UN1950, AEROSOLS, 2.1

15 Regulatory information

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
14807-96-6	Talc (Mg3H2(SiO3)4)

· **TSCA (Toxic Substances Control Act):**

68476-86-8	Petroleum gases, liquefied, sweetened
108-88-3	toluene
79-20-9	methyl acetate
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
67-64-1	acetone
69430-35-9	Alicyclic hydrocarbon resin
9017-27-0	Alpha-methyl styrene/vinyl toluene copolymer
14807-96-6	Talc (Mg3H2(SiO3)4)
66070-58-4	Styrene-Ethylene/Butylene-Styrene block Copolymer
1333-86-4	Carbon black
8042-47-5	White Mineral oil
6683-19-8	Tertrakis(methylene(3,5-di(tert)-butyl-4-hydroxyhydrocinnamate)) methane

· **Proposition 65**

· **Chemicals known to cause cancer:**

1333-86-4	Carbon black
-----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

108-88-3	toluene	II
67-64-1	acetone	I

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
14807-96-6	Talc (Mg3H2(SiO3)4)	3

(Contd. on page 10)



Trade name: 40523 Low VOC Rubberized Undercoating

(Contd. of page 9)

1333-86-4	Carbon black	2B
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· TLV (Threshold Limit Value established by ACGIH)		
108-88-3	toluene	A4
67-64-1	acetone	A4
14807-96-6	Talc (Mg3H2(SiO3)4)	A4
1333-86-4	Carbon black	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
1333-86-4	Carbon black	
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		
· Chemical safety assessment A Chemical Safety Assessment has not been carried out.		

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Environment protection department.

· **Contact:** Steve Gaver

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent