

LPS[®] ELECTRO 140[°]

CONTACT CLEANER



Conforms to:
 Bombardier (Canadair) CMS 570-01
 Learjet LES 1239
 McDonnell Douglas CSD #1

FEATURES

- Flash point above 140°F (60°C)
- Superior wetting and penetrating action
- Controlled evaporation
- No residue
- Non-conductive
- Safe to use on most surfaces
- Ideal for parts washer, dip tanks and ultrasonic cleaning tank
- Inverta Spray Valve

PACKAGES

Net Fill
 11 oz. (312 grams) aerosol

Part No.
 00916



APPLICATIONS

- Coin Counters & Chutes
- Connectors
- Contacts
- Fluid Systems
- Office Equipment
- Printed Circuits
- Relays and Controls
- Semiconductor Assemblies
- Switches
- Telephone Equipment

PROPERTIES

Appearance/Physical State:
 Clear liquid

Dielectric Strength
 (ASTM D-877):
 15.14 kV

Flash Point (TCC):
 144°F (62°C)

HMIS:
 1, 2, 0

Surface Tension:
 25.9 dynes/cm @ 77°F (25°C)

Propellant:
 CO₂

Specific Gravity:
 0.79

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE: WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2010 LPS Laboratories • LPS[®] is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2086 • Rev. 10/2010