

G704B-SR & G704B-40SH CherryMAX® Split Power Riveters



G704B-SR

*3' Hose,
Inline Head*

*Perfect For Limited
Access Areas*



G704B-40SH

*10' Hose,
Pistol Grip Head*

The CherryMAX G704B-SR & G704B-40SH split power riveters were designed specifically for the installation of CherryMAX rivets in applications with extremely limited access.

The tool transmits power from the power unit through a flexible hose to a small, lightweight head. By utilizing the proper pulling head, design problems and operator fatigue can be greatly reduced.

The SR model is equipped with a three foot hose and the 40SH model is equipped with an eight foot hose.

Specifications

Air Pressure 90 PSI (6.2 bar) min./110 PSI (7.6 bar) max.

Noise Level does not exceed 85 dB (A)

Air Consumption 4 CFM @ 20 cycles per minute

G704B-SR & G704B-40SH Split Power Riveters				
Part Number	Hose Length	Stroke	Pulling Force	Weight
G704B-SR	3' (91.5 cm)	.518"	3136 lbs (1423 kgs)	4.5 lbs (2.0 kgs) (power unit only)
G704B-40SH	10' (305 cm)			

G704B-SR & G704B-40SH Pulling Heads

- Pulling heads not included with riveter, please order from charts below.
- New, interchangeable nosepiece pulling heads also available on page 114.
- For full specs on pulling heads below please see pages 115-116.

G704B-SR & G704B-40SH Pulling Heads				
Part Number	Head Style	Rivet Type	Rivet Diameters	Max. Grip
H701B-456	Straight	CherryMAX	1/8", 5/32", 3/16" **	All
		CherryMAX 'AB'	1/8", 5/32", 3/16" †	-4 *
		MBC L/C	1/8", 5/32", 3/16"	-4 *
		SST	1/8", 5/32", 3/16" **	All
H753A-456	Right Angle	CherryMAX	1/8", 5/32", 3/16" **	All
		CherryMAX 'AB'	1/8", 5/32", 3/16" †	-4
		SST	1/8", 5/32", 3/16" **	All
H781-456	Offset	CherryMAX	1/8", 5/32", 3/16" **	All
		CherryMAX 'AB'	1/8", 5/32", 3/16" †	-4 *
		SST	1/8", 5/32", 3/16" **	All

G704B-SR & G704B-40SH Pulling Heads					
Part Number	Head Style	Required Adapter	Rivet Type	Rivet Diameters	Max. Grip
H9015-3C	Straight	704A9	MS ††	3/32"	-4 *
H9015-4C	Straight	704A9	MS ††	1/8"	-4 *
H9015-5C	Straight	704A9	MS ††	5/32"	-4 *
H9015-6C	Straight	704A9	MS ††	3/16"	-4 *
H955-3	Straight	—	CherryLOCK 'A'	3/32" †	-4 *
H955-4	Straight	—	CherryLOCK 'A'	1/8" †	-4 *
H955-5	Straight	—	CherryLOCK 'A'	5/32" †	-4 *
H955-6	Straight	—	CherryLOCK 'A'	3/16" †	-4 *
H746A-4MBC	Straight	—	Std. MBC	1/8"	-4 *
H746A-5MBC	Straight	—	Std. MBC	5/32"	-4 *
H746A-6MBC	Straight	—	Std. MBC	3/16"	-4 *

* May be double stroked for longer grips. ** Nominal and oversize.
 † Will not install 3/16" diameter aluminum (stainless steel & monel only). †† Serrated stems only.