

PRODUCT DATA SHEET

ACETONE PTI-ACT SOLVENT

DESCRIPTION

Acetone (dimethyl ketone and 2-propanone) is a clear, colorless, low-boiling, flammable, volatile liquid, characterized by rapid evaporation and a faintly aromatic odor. It is readily miscible in most organic solvents and completely miscible, in all proportions, in water. Acetone is an excellent solvent for a wide range of gums, resins, waxes, fats, greases and oils. It is ideal for thinning fiberglass resin, cleaning fiberglass tools and dissolving two-part epoxies and superglue before hardening. It is used as a volatile component and thinner for some paints and varnishes. As a heavy-duty degreaser, it is useful in the preparation of metal prior to painting; it also thins polyester resins, vinyl and adhesives.

SOLVENT PROPERTIES & CHARACTERISTICS

Boiling Point	133°F
Flash Point (open cup)	-17°C
Weight (lbs per gallon)	6.6 lb
Color	Clear
Volatile Organic Compounds (VOC)	0 g/L
Specifications	O-A-51H, ASTM D329

SHELF LIFE

Shelf life is only applicable for materials stored in unopened and undamaged original factory filled containers. 1 year when stored between 50°-85° Fahrenheit.

HEALTH, SAFETY, & STORAGE REQUIREMENTS

Refer to each individual material SDS (Safety Data Sheet) for specific requirements on the health, safety, storage and handling requirements. Follow all local, state, and national regulations during surface preparation, material application and cleanup.

PRODUCT INFORMATION & DISCLAIMER

Product Data Sheets are periodically updated to reflect new information. It is important to use the latest and most recent revision for the product being used. The foregoing information is accurate to the best of our knowledge. However, due to differences in customer handling, use and method of application which are not known and are beyond our control, Products Techniques, Inc. makes no warranties as to the end result.