

PRODUCT DATA SHEET

TOOTH MARKING GREASE PTI LUBRICANT SERIES

DESCRIPTION

Tooth Marking Grease is an Ester Based Oil with high pigmentation loading. Although the Tooth Marking Grease has the consistency of a thick paste, it may be thinned or thickened to meet your requirements. This product is formulated to be applied to gears. The Tooth Marking Grease is a "preventative maintenance" item which helps to not only lubricate your gears under extreme conditions but also to help identify when more lubrication is need before excessive friction causes degradation or shortening of the gear teeth occur.

COLORS

This grease comes in a white color.

SHELF LIFE

Shelf life is only applicable for materials stored in unopened and undamaged original factory filled containers. 1 year when stored between 50°-85° Fahrenheit.

APPLICATION

Wipe off any pre-existing grease or oil and then solvent wipe with a clean, lint free cloth. You can also remove old lubricants with PTC-2001, PTC-2002, Bizzy-BTM or MotoSpaTM. Blow out solvent, cleaner or degreaser residue with high-pressure air to prevent contamination to techlube grease. Blasting with 120-mesh aluminum oxide grit is desirable if previous lubricant has formed heavy gum deposits. Apply the grease with a brush, spatula, grease gun or rag. No curing is required. All materials covered by this specification are ready for use immediately after application.

NOTE: Application of PTI products requires the use of all OSHA approved safety equipment, including proper ventilation. Additionally, PTI products require the recommended temperature/humidity conditions and film thickness ranges for optimal performance. The material, hangar, and aircraft skin temperatures should be no lower than 75° F / 25° C before, during and after application.

HEALTH, SAFETY, & STORAGE REQUIREMENTS

Refer to each individual material SDS (Safety Data Sheet) for specific requirements on the health, safety, storage and handling requirements. Follow all local, state, and national regulations during surface preparation, material application and cleanup.

PRODUCT INFORMATION & DISCLAIMER

Product Data Sheets are periodically updated to reflect new information. It is important to use the latest and most recent revision for the product being used. The foregoing information is accurate to the best of our knowledge. However, due to differences in customer handling, use and method of application which are not known and are beyond our control, Products Techniques, Inc. makes no warranties as to the end result.

PTI-ASG_PDS_Rev. 01 7/31/2012